



## TDR-15 Tri-Deck Roller Finishing Mower

**VERSATILITY + QUALITY of CUT**

Progressive's Tri-Deck 15' finishing mower (**TDR-15**) has long been the sod professionals choice for a wide area mower for mid-size operations and fields.

This versatile mower can cut as low as ½" without scalping. Full length 6" diameter rollers front and back follow the ground contours and help prevent scalping while they smooth the field surface and aid in moisture retention. Standard roller wipers prevent build up in damp conditions.

The superior cut quality comes from the combination of high lift blades that create enough vacuum to lift the grass for a clean even cut and disperse the clippings evenly over the rollers. Easy access to height adjusters makes setting the height of cut a snap.

The **TDR-15** is another example of the ingenuity and quality that goes into producing a durable, reliable rotary finishing mower that is easy to maintain. The **TDR-15** not only provides versatility of use and quality of construction, it is "**The Better Built Choice**".



*The Better Built Choice.™*

**Pro Lift-N-Turn™**

The productivity advantage of Progressive's exclusive **Pro Lift-N-Turn™** system is standard equipment. Operators have the ability to temporarily raise the decks off the ground with the PTO still engaged, making turning easier on the turf and the operator more productive. An automatic mechanical stop prevents the main decks from raising too far. The result is less damage from dragging the rollers across the turf. Progressive's **Pro Lift-N-Turn™** has simply eliminated the issues competitive roller mowers face when turning.



**Easy change height adjustment:**

Infinite cutting height adjustment from ½" to 4" is easily accomplished with the supplied tool. This allows the mower to transition quickly for multiple mowing height applications. The durable design resists rusting and wear. Design allows for a 0" uncut circle (zero turning radius).



**Full length rollers:**

6" diameter rollers running the full length on both the front and rear of each mower deck, helps to smooth the mowing surface while cutting. Roller end bearings are sealed and use HEX style drive to ensure positive engagement and long life. The rollers can also stripe the turf for a pleasing visual impact for the facility's patrons - a testament to the professionalism of the job.



**Simpler Maintenance = Lower Cost:**

Maintenance Free Blade Spindles are used to both lower cost and time spent on routine maintenance. They also provide peace of mind that a missed greasing won't render the mower out of service.

**C.V. Equipped Input PTO:**

Often mowers of this size are moved between tractors that are equipped with different size tires. This created additional work when the mower was connected as either the mower or the tractor's drawbar had to be adjusted to achieve the proper drive line positioning. To overcome this, Progressive has equipped the TDR-15 with a constant velocity (CV) input PTO as standard equipment. This makes connecting the mower to a tractor easier as. The result: overall connection time is greatly reduced!



**TDR-15 Tri-Deck Roller Mower Specifications**

**Part Number:** 528750B standard painted decks  
**Cutting Width:** 15.5 feet  
**Mowing Capacity:** 2 mph 3.75 acres per hour\*  
 4 mph 7.5 acres per hour\*  
 6 mph 11.3 acres per hour\*  
**Transport Tires:** P275 / 60R 15 Automotive radials

**Recommended PTO H.P.:** 30 to 50  
**Transport Width:** 97"  
**Transport Height:** 7' 10"  
**Transport Length:** 14'  
**Operating Weight:** 3,725 lb.

\*Assumes no overlap or turning

Under our policy of continuous improvement, we reserve the right to change specifications and designs without prior notice. The illustrations shown do not necessarily represent the standard version of product offered by Progressive Turf Equipment Inc.

**(800) 668-8873      (519) 527-1080      FAX: (519) 527-2275**  
[www.progressiveturfequip.com](http://www.progressiveturfequip.com)    [info@progressiveturfequip.com](mailto:info@progressiveturfequip.com)